



SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

Swancorp Group Pty Ltd

Chemwatch: 4563-54

Version No: 5.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 20/06/2022

Print Date: 06/12/2023

L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES
Chemical Name	Not Available
Synonyms	S elemental; flowers of sulfur; flour sulphur; flower colloidal precipitated; sublimed sulphur; atomic sulphur; brimstone; roll; powder
Chemical formula	S
Other means of identification	Not Available
CAS number	7704-34-9.

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Used in the manufacturing of sulfuric acid, carbon disulfide, sulfites, insecticides, plastics, enamels, metal-glass cements; in vulcanizing rubber; syntheses of dyes; making gun powder and matches.
--------------------------	--

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Swancorp Group Pty Ltd
Address	123 Boundary Road Rocklea QLD 4106 Australia
Telephone	+61 7 3276 7422
Fax	+61 7 3276 8622
Website	Not Available
Email	Not Available

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+61 1800 951 288	+61 1800 951 288
Other emergency telephone numbers	+61 2 9186 1132	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Not Applicable

CLASSIFIED AS A DANGEROUS GOOD FOR STORAGE IN WESTERN AUSTRALIA ONLY

UN No: 1350

DG Class: 4.1

Packing Group: III

HAZCHEM: 1Z

Subrisk: Not Applicable

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

CAS No	%[weight]	Name
7704-34-9.	100	<u>sulfur granules, pellets, prills, flakes, pastilles</u>

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L;
* EU IOELVs available

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Sulfur dioxide inhalation is a potential hazard in fire situations. Sensitive persons can experience skin irritation from repeated exposure to the sulfur dust. Allergic responses can occur.
[Genium]
Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Incipient fires in sulfur storage piles can be frequently smothered by gently shoveling more sulfur, sand, or fine earth on them to exclude all air.
- ▶ For larger fires, water applied as a fine mist is the most useful agent. High pressure water sprays disperse the dust into the air and should NOT be used. Coarser water sprays are permissible on deposits containing only a small proportion of extreme sulfur fines. Large fires can be smothered by experts using additional sulfur (since SO2 decomposition product does not support combustion).
- ▶ Steam or inert gases (such as carbon dioxide) are excellent extinguishers for use in containers that can be closed tightly. Care should be taken that the sulfur dust is not scattered into the air.
- ▶ If a container is closed tightly and the volume of oxygen enclosed is not too large, a fire will be put out by the sulfur dioxide formed. Sulfur dioxide is a toxic gas.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

Advice for firefighters

Fire Fighting	For fires involving sulfur: ▶ Do not use solid streams of water; which could create sulfur dust clouds and cause an explosion or move burning sulfur to adjacent areas. Fire will rekindle until mass is cooled below 145 C. ▶ Cool containers, tank cars, or trailer loads with flooding quantities of water until well after fire is out. ▶ Once a fire is controlled, post fire watch for at least 4 hours. Small fires are easy to miss and can linger for hours. Re-ignition may occur. ▶ Firemen exposed to contaminated smoke should be immediately relieved and checked for symptoms of exposure to toxic gasses. <i>Seek medical attention immediately!</i> . This should not be mistaken for heat exhaustion or smoke inhalation. These are extremely irritating to the respiratory tract and may cause breathing difficulty and pulmonary edema. Symptoms may be delayed ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: sulfur oxides (SOx) sulfur dioxide (SO2) NOTE: Burns with intense heat. Produces melting, flowing, burning liquid and dense acrid black smoke. ▶ Sulfur fires are deep blue at night, with very short flames. Fire is invisible by daylight except for smoke and heat. Burning material, however,

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

	turns a deep red-black.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Clean up all spills immediately. ▶ Avoid contact with skin and eyes. ▶ Wear impervious gloves and safety glasses. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Do NOT use air hoses for cleaning ▶ Place spilled material in clean, dry, sealable, labelled container.
Major Spills	▶ Sulfur dusts form an explosive mixture with air which may be ignited by static electricity. ▶ Explosion may be avoided by preventing atmospheres becoming dust-laden by adequate ventilation or by hose-down instead of sweeping. ▶ If mixture with incompatible materials is likely, evacuate personnel to a safe distance. ▶ Keep product moist to suppress both fire and dust potential. ▶ Recover material without delay using non-sparking hand tools. ▶ Place recovered materials in clean, labelled closed containers. ▶ Keep contents damp. ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Control personal contact with the substance, by using protective equipment and dust respirator. ▶ Prevent spillage from entering drains, sewers or water courses. ▶ Avoid generating dust. ▶ Sweep, shovel up. Recover product wherever possible. ▶ Put residues in labelled plastic bags or other containers for disposal. ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ Molten sulfur should be maintained at temperatures between 115 deg. minimum, to prevent accumulation of solid sulfur, and 145 deg. maximum, to prevent sulfur fires inside tank. ▶ Dedicated heated and vented tanks are required. ▶ Molten sulfur must not be loaded into containers that contain hydrocarbons or moisture. ▶ Taking precautions to prevent sparking when tank covers are released. ▶ Open slowly and allow tanks to vent accumulated highly flammable hydrogen sulfide gas if present ▶ Limit all unnecessary personal contact. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry area protected from environmental extremes. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: ▶ Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams). ▶ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Lined metal can, lined metal pail/ can. ▶ Plastic pail. ▶ Polyliner drum. ▶ Packing as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks. ▶ Glass container is suitable for laboratory quantities
--------------------	---

Continued...

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

Storage incompatibility

Avoid contamination of water, foodstuffs, feed or seed.

Sulfur:

- ▶ is both an oxidising agent and a reducing agent
- ▶ when finely divided and dry, forms explosive mixtures with air
- ▶ when molten can generate hydrogen sulfide and carbon disulfide when in contact with some organic materials.
- ▶ is a flammable substance in both the solid and liquid states; the dust is characterised by a very low ignition point of 190 C compared to other combustible dusts - dust clouds are readily ignited by weak frictional sparks if the oxygen content is above 8%.
- ▶ vapours react violently with lithium carbide
- ▶ forms explosive and extremely sensitive mixtures with most oxidising substances such as chlorates, nitrates, perchlorates and permanganates; mixtures may be extremely sensitive to friction or vibration.
- ▶ reacts violently with many substances, including strong oxidisers, aluminium powders, boron, bromine pentafluoride, bromine trifluoride, calcium hypochlorite, carbides, caesium, chlorates, chlorine dioxide, chlorine trifluoride, chromic acid, chromyl chloride, dichlorine oxide, diethylzinc, fluorine, halogen compounds, hexalithium disilicide, lampblack, lead chlorite, lead dioxide, lithium powdered nickel, nickel catalysts, red phosphorus, phosphorus trioxide, potassium, potassium chlorite, potassium iodate, potassium peroxyferrate, rubidium acetylide, ruthenium tetroxide, sodium, sodium chlorite, sodium peroxide, tin, uranium, zinc, zinc(II) nitrate, hexahydrate
- ▶ forms friction-, impact- and shock- sensitive explosive or pyrophoric mixtures with ammonia, ammonium nitrate, barium bromate, bromates, calcium carbide, charcoal, hydrocarbons, iodates, iodine pentafluoride, iodine pentoxide, iron, lead chromate, mercurous oxide, mercury nitrate, mercury oxide, nitryl fluoride, nitrogen dioxide, inorganic perchlorates, potassium bromate, potassium nitride, potassium perchlorate, silver nitrate, sodium hydride, sulfur dichloride
- ▶ is incompatible with barium carbide, calcium, calcium carbide, calcium phosphide, chromates, chromic acid, chromic anhydride, 1,5-dinitronaphthalene, hafnium, indium, iodates, iodic acid, iodine oxide, lead chlorate, lithium acetylide, mercury oxide, mercuric nitrate, palladium, potassium permanganate, silver bromate, silver chlorate, silver oxide, sodium, strontium carbide, thallium oxide, thorium, thorium dicarbide
- ▶ attacks copper, mercury, silver
- ▶ when molten reacts with air forming sulfur dioxide, and with hydrogen, forming hydrogen sulfide; explosion may occur
- ▶ may accumulate static electrical charges; vapours may ignite

NOTE: Dusts containing 25% or more elemental sulfur may be almost as explosive as pure sulfur.

Sulfur will form sulfides with most metals, including iron, and reacts vigorously with metals in the sodium and magnesium groups on the periodic table. Sulfides of iron will oxidise fairly rapidly in moist air. In the presence of other readily oxidised combustibles (such as some oily materials) under certain conditions, the heat liberated may be sufficient to result in spontaneous ignition. This phenomenon has not been observed with pure sulfur products or disintegrating sulfur in contact with unprotected steel at ordinary ambient temperatures. Inadvertent mixtures of sulfur, iron, and miscellaneous oils should be avoided. Oxidation is accelerated by higher temperatures. Heat buildup and ignition can be prevented by keeping the sulfides wet until oxidation is complete.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
sulfur granules, pellets, prills, flakes, pastilles	Not Available	Not Available

MATERIAL DATA

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]

This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or *poorly soluble** in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e., are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload)

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

- ▶ Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

► If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:

- (a): particle dust respirators, if necessary, combined with an absorption cartridge;
- (b): filter respirators with absorption cartridge or canister of the right type;
- (c): fresh-air hoods or masks.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

Air Speed:

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)

1-2.5 m/s (200-500 f/min.)

grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

Upper end of the range

1: Room air currents minimal or favourable to capture

1: Disturbing room air currents

2: Contaminants of low toxicity or of nuisance value only.

2: Contaminants of high toxicity

3: Intermittent, low production.

3: High production, heavy use

4: Large hood or large air mass in motion

4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields
- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

- Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber.
- butyl rubber.

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

	▸ fluorocarbon. ▸ polyvinyl chloride. Gloves should be examined for wear and/ or degradation constantly.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: ▸ Overalls. ▸ Barrier cream. ▸ Eyewash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	- -	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	Bright yellow solid, as prills, granules, pellets, flakes or pastilles; insoluble in water. Slightly soluble in alcohol and ether. Soluble in carbon disulfide, benzene and toluene. Odourless, but impurities may cause H ₂ S smell. Sulfur is not subject to the provisions of the ADG Code when it is transported in quantities of less than 400 kg per package, or when it has been formed into a specific shape (e.g. prills, granules, pellets, pastilles or flakes). [Special Provision 242].		
Physical state	Divided Solid	Relative density (Water = 1)	1.92-2.07
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	232 (as dust)
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	112.8-119	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	444.6 (IBP)	Molecular weight (g/mol)	32.06
Flash point (°C)	>180 (as dust)	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	1400 g/m ³ dust	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	35 g/m ³ dust	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	0.133 @ 184 deg	Gas group	Not Available
Solubility in water	Insoluble	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. There is no evidence that systemic poisoning results from inhalation of sulfur dust. Sulfur vapour irritates both the upper and lower respiratory passages and if inhaled may cause coughing, conjunctivitis, nausea,vomiting and chest tightness, bronchitis and in extreme pulmonary oedema (sudden or delayed). Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.	
Ingestion	Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Ingested sulfur is converted to sulfides in the gastrointestinal tract, and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur. Swallowing large amounts may cause nausea and vomiting.	
Skin Contact	This may aggravated by perspiration or moisture. The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.	
Eye	The dust may irritate the inner surfaces of the eyelids. Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.	
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Sensitive persons can experience skin irritation from repeated exposure to the sulfur dust. Allergic responses can occur. Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray.	
sulfur granules, pellets, prills, flakes, pastilles	TOXICITY	
	dermal (rat) LD50: >2000 mg/kg ^[1]	IRRITATION
	Inhalation(Rat) LC50: >5.43 mg/L4h ^[1]	Eye (human): 8 ppm irritant
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin: adverse effect observed (irritating) ^[1]
	Skin: no adverse effect observed (not irritating) ^[1]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✔ – Data available to make classification

SECTION 12 Ecological information

Toxicity

sulfur granules, pellets, prills, flakes, pastilles	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	>0.005mg/L	2
	LC50	96h	Fish	>207mg/L	4
	NOEC(ECx)	504h	Crustacea	>0.003mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
------------	-------------------------	------------------

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

Ingredient	Persistence: Water/Soil	Persistence: Air
sulfur granules, pellets, prills, flakes, pastilles	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
sulfur granules, pellets, prills, flakes, pastilles	LOW (LogKOW = 0.229)

Mobility in soil

Ingredient	Mobility
sulfur granules, pellets, prills, flakes, pastilles	LOW (KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	--

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
sulfur granules, pellets, prills, flakes, pastilles	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
sulfur granules, pellets, prills, flakes, pastilles	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

sulfur granules, pellets, prills, flakes, pastilles is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Additional Regulatory Information

Not Applicable

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

National Inventory Status

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (sulfur granules, pellets, prills, flakes, pastilles)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (sulfur granules, pellets, prills, flakes, pastilles)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	20/06/2022
Initial Date	16/06/2006

SDS Version Summary

Version	Date of Update	Sections Updated
3.1	16/06/2006	Hazards identification - Classification, Identification of the substance / mixture and of the company / undertaking - Supplier Information
5.1	20/06/2022	Expiration. Review and Update

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

SULFUR GRANULES, PELLETS, PRILLS, FLAKES, PASTILLES

- ▶ PC—TWA: Permissible Concentration-Time Weighted Average
- ▶ PC—STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.